

# VBH22 WITH BCU9702



## BASIC DATA:

Battery: 1800mAh/3.7V

Output nom.: 24VDC

Max blind size: 4m<sup>2</sup>

Up to 200 full cycles/charge

Magnetic holder

Charged via micro USB

Blue LED indicators

Low batt indicator

Optional solar cell for charging by sunlight

Fully electronic stops



## VBH22 BLIND SYSTEM:

22mm cavity

12.5mm aluminum slats

24V DC encoded motor

Up to 4m<sup>2</sup> units

Up to 3000mm wide

Up to 3000mm height

Minimum width of 380mm

Available in all standard colors

The VBH22 system, is a blind system, encapsulated in a sealed 2 or 3 layer glass unit, protecting the blind from damage, and makes shading and hygiene superior to other solutions.

The control system is a basic solution, operated by a simple battery control unit, mounted directly on the glass or frame of the window, and needs only to be connected to the motor inside.

No powercables, programming or configuration is needed, the system is ready to operate, right upon installation.

The control unit is mounted on a magnetic bracket, and is easily detachable, for charging.

A standard motorcable, are used for connecting between the blind and controller, and with a diameter of 4mm, it is easily fittable.

The system is designed, so any controller can operate any blind. This means that it doesn't matter, if controllers are being mixed around during charging, or for larger projects, you can keep a few extra controllers always charged, ready to re-place empty ones.

## ORSHADE

Orshade Electronics Ltd  
15, Shaked Str.  
Hevel Modiin industrial Park  
IL73199 Shoham

Phone: +972 3 9702188  
Fax: +972 3 9702180

Mail: [info@orshade.eu](mailto:info@orshade.eu)  
Web: [www.orshade.com](http://www.orshade.com)